

Containers Container Specs	8' DV ISO Standard	10' DV ISO Standard	20' DV ISO Standard	40' DV ISO Standard	45' DV ISO Standard	20' Open Top ISO - Standard	20' HC Open Top ISO - Standard	40' Open Top ISO - Standard	20' OPEN SIDE	40' HC OPEN SIDE
Max. Gross Weight	6,000 Kg	8,860 Kg	30,480 Kg	30,480 Kg	34,00 Kg	30.480 kg	30.480 kg	30.480 kg	24,000 kgs	24,000 kg
Tare. Weight	950 Kg	1,300 Kg	2,200 Kg	3,820 Kg	4,860 Kg	2.330 kg	2.350 kg	4.000 kg	3,180 kgs	5,700 kg
Max. Payload	5,050 Kg	10,160 Kg	28,350 Kg	26,660 Kg	29,140 Kg	28.150 kg	28.150 kg	26.480 kg	20,820 kgs	18,300 kg
External Dimensions										
Length	2,438 mm	2,991 mm	6,058 mm	12,192 mm	13,716 mm	6.058 mm	6.058 mm	12.192 mm	6,058 mm	12,192 mm
Width	2,200 mm	2,438 mm	2,350 mm	2,438 mm	2,500 mm	2.438 mm	2.438 mm	2.438 mm	2,438 mm	2,438 mm
Height	2,260 mm	2,591 mm	2,390 mm	2,591 mm	2,896 mm	2.591 mm	2.896 mm	2.591 mm	2,591 mm	2,896 mm
Internal Dimensions										
Length	2,275 mm	2,831 mm	5,898 mm	12,032 mm	13,559 mm	5.898 mm	5.898 mm	12.032 mm	5,898 mm	12,031 mm
Width	2,106 mm	2,344 mm	2,350 mm	2,352 mm	2,432 mm	2.350 mm	2.350 mm	2.350 mm	2,287 mm	2,288 mm
Height	2,050 mm	2,376 mm	2,390 mm	2,393 mm	2,700 mm	2.350 mm	2.695 mm	2.350 mm	2,299 mm	2,547 mm
Door opening Dimensions										
Width	1,440 mm	2,330 mm	2,330 mm	2,340 mm	2,420 mm	2.338 mm	2.338 mm	2.338 mm	2,114 mm	2,280 mm
Height	2,125 mm	2,280 mm	2,280 mm	2,280 mm	2,587 mm	2.280 mm	2.585 mm	2.280 mm	2,169 mm	2,343 mm
Internal cubic capacity										
Internal cubic capacity	10,00 m ³	16,00 m ³	33,00 m ³	67,70 m ³	89,03 m ³	32,6 m ³	32,6 m ³	66,4 m ³	32,6 m ³	67,6 m ³
Top Opening Dimensions										
Width	--	--	--	--	--	2.230 mm	2.230 mm	2.230 mm	--	--
Height	--	--	--	--	--	5.672 mm	5.672 mm	11.806 mm	--	--
Side opening										
Width	--	--	--	--	--	--	--	--	5,702 mm	11,970 mm
Height	--	--	--	--	--	--	--	--	2,154 mm	2,240 mm
	** ALL CONTAINERS ARE <u>CSC certified by Classification Society (GL, BV, ABS, LR, NV)</u>									

Reefers Reefer Specs	Reefer 10ft	Reefer 20ft	Reefer 40ft	Reefer High Cube 40ft	45ft High Cube	45ft High Cube PalletWide
Max. Gross Weight	15.000 kg	30.480 kg	32.500 kg	34.000 kg	34.000 kg	34.000 kg
Tare. Weight	2.030 kg	2.900 kg	4.500 kg	4.650 kg	5.995 kg	6.240 kg
Max. Payload	12.970 kg	27.580 kg	25.980 kg	29.350 kg	27.550 kg	27.260 kg
External Dimensions						
Length	2.991 mm	6.058 mm	12.192 mm	12.192 mm	13.716 mm	13.716 mm
Width	2.438 mm	2.438 mm	2.438 mm	2.438 mm	2.556 mm	2.600 mm
Height	2.591 mm	2.591 mm	2.591 mm	2.896 mm	2.896 mm	2.950 mm
Internal Dimensions						
Length	2.388 mm	5.450 mm	11.500 mm	11.583 mm	13.275 mm	13.290 mm
Width	2.290 mm	2.292 mm	2.200 mm	2.292 mm	2.438 mm	2.498 mm
Height	2.276 mm	2.288 mm	2.230mm	2.545 mm	2.562 mm	2.629 mm
Door opening Dimensions						
Width	2.294 mm	2.292 mm	2.232 mm	2.292 mm	2.441 mm	2.494 mm
Height	2.265 mm	2.265 mm	2.252 mm	2.562 mm	2.552 mm	2.594 mm
Internal cubic capacity	12,4 m ³	28,6 m ³	56,4 m ³	67,6 m ³	83,1 m ³	87,2 m ³
More specs						
	<ul style="list-style-type: none"> * Connection with diesel engines (independent power source) * Exterior walls of aluminum. * Double door with rod-bars. * Control mechanism: in the back of the container. 	<ul style="list-style-type: none"> * Connection with diesel engines (independent power source) * Entirely Corten steel. * Double door with rod-bars. * Control mechanism: in the back of the container. <li style="color: red;">For 45ft HC : Euro pallets: 33 <li style="text-align: center;">ISO pallets: 26 				